

FIBERGLASS JOINT TAPE:

Ideal material for dealing with joint of drywall, cement board, calcium silicate board, etc.

SPECIFICATION:

Material: E-glass or C-glass

Color: white (standard), custom color

Construction: Leno

Weight: 60g/sqm, 65g/sqm, and 75g/sqm, up to 120g/m²

Counts: 9x9/inch, 8x8/inch

Width: 25mm, 48mm, 50mm, 100mm, up to 1220mm

Roll length: OEM according to specifications



Mesh	W x L	Weight	Roll Dia.:cm	Rolls/ctn	Ctn size:cm	20FCL Quantity
9x9/inch	5cmx20m	70g/sqm	8.6-8.8	100	45x45x21	715 Cartons
9x9/inch	5cmx45m	70g/sqm	10.1-10.3	54	33x33x32	833 Cartons
9x9/inch	5cmx90m	70g/sqm	14.1-14.3	24	44x30x21	1,001 Cartons
8x8/inch	5cmx20m	65g/sqm	8.1-8.3	100	43x43x21	715 Carton
8x8/inch	5cmx45m	65g/sqm	9.1-9.3	54	30x30x32	931 Carton
8x8/inch	5cmx90m	65g/sqm	13.1-13.3	24	42x28x21	1232 Carton
8x8/inch	5cmx20m	60g/sqm	8.1-8.3	100	43x43x21	715 Carton
8x8/inch	5cmx45m	60g/sqm	9.1-9.3	54	30x30x32	931 Carton
8x8/inch	5cmx90m	60g/sqm	13.1-13.3	24	42x28x21	1232 Carton

Paper Joint Tape

Paper Joint Tape, ideal for reliable reinforcement of the plasterboard joints when applying a gypsum joint

- The materials' high elastic potential prevents the appearance of cracks on the joint when foundation movement occurs.
- The micro-perforations along the entire surface of the tape ensure a strong and easy bond to the joint filler.
- Factory-fitted core, for effortless folding along its length and a stable reinforcement of internal corners.

Specifications:

Width: 50mm

Length: 100m, 150m



Aluminum paper corner tape

Aluminum paper corner tape is a flexible paper tape roll with two metal strips as reinforcement. Intended for reinforcing the inner and outer corners in dry construction systems. The tape is bent inwards or outwards from the middle and is applied to interior or exterior corners to reinforce the edges of dry construction systems.

Advantage:

Flexible structure.

Easy to apply.

Creates perfectly straight corners

Specifications:

Width: 50mm

Length: 30m



Joint Compound

Joint Compound is a gypsum base ready mix joint compound that may be used directly from the container. All Purpose Joint Compound is designed for tape application, fastener spotting and complete joint finishing of gypsum board. It can also be used to repair cracks in plastered walls, to texture surfaces and to laminate gypsum board to other surfaces such as masonry or other gypsum board. It contains sufficient binder to secure the reinforcing tape and develops its strength and hardness by drying.

Specifications:

25kgs/pail



Joint Filler

Joint filler is a gypsum-based jointing compound for manual jointing with a joint tape of plasterboards. It is suitable for complete skim coating or filling small cracks.

Application

For filling and finishing joints between gypsum boards

Suitable for complete skim coating

Filling of small cavities and repairs

Application in premises with normal humidity

Specifications:



25kgs/bag

Advantage

High level of smoothness and smoothness of joint
Economical and easy to work with
Provides strong and durable bond between boards
Limited shrinking during storage

Drywall screws for plasterboard wall partition:

Drywall Screw, corrosion resistant, designed for fixing plasterboards to metal profiles with metal thickness up to 0.7 mm.

1. Diameter: 3.5mm/3.9mm/4.2mm/4.8mm
2. Length: 16mm--152mm
3. Material: Steel C1022A
4. Finish: Black or Grey phosphate; White zinc plated
5. Packing: 1000pcs/500pcs/box or bulk packing in 15-20kg cartons with pallets



Self-drilling screw

Self-drilling screw with flat head is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. Fasten elements with a collective thickness up to 2 mm.

Size: 4.2mm x 13mm

Packing: 1000pcs/box



Self-drilling screw

Self-drilling screw with wafer head is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. Fasten elements with a collective thickness up to 2 mm.

Size: 4.2mm x 13mm

Packing: 1000pcs/box

